



Climate-Controlled Gemrik DEF Shelter by Fluidall For Bulk Storage & Dispense of Diesel Exhaust Fluid

DEFGR330TI - Includes (1) 330 Gallon IBCs Standard Features

BUILD SPECIFICATIONS INCLUDE

- CNC Precision Cut Powder Coated Aluminum
- Blue Color
- Footprint 48"W x 76.75"L x 78"H
- Stainless Steel Rivets and Fastening Components
- Fully Assembled for E-Z Installation & Set-Up
- 4" Side Accessible Forklift Base Frame
- Solid Floor
- Gas Shock Assisted Side Access Door/s (per model size)
- Large Lockable Dispense Equipment Access Door
- Unit Anchoring Points
- 4 GFCI-15A Dual Duplex Interior Electrical Receptacles
- Manual Shut-Off to Interior Electrical Receptacle Box
- Single Phase, 115V Exterior Junction Box
- Heater With Thermostat
- Insulated Top & Walls

STORAGE & DISPENSE COMPONENTS INCLUDED

- One IBC 330 Gallon Caged Tote
- Total Capacity 330 Gallons
- Sealed Closed Loop Micro-Matic Dispense and Fill System
- Self-Priming Graco DEF Pump
- Graco Digital Meter
- Stainless Steel Automatic Shut-Off Dispense Nozzle
- 33' Hose Reel
- All Fill & Dispense Components are Connected & Ready to Fill & Dispense

AVAILABLE OPTIONS

- Pulse Out Meter

**Materials, Standards, and Options are subject to change
for equal or better items without notice.